

AD-A225 864

DTIC FILE COPY

2

OFFICE OF NAVAL RESEARCH

Contract N00014-84-K-0021

Technical Report No. 22

FINAL REPORT

by

J. K. Gillham

Polymer Materials Program
Department of Chemical Engineering
Princeton University
Princeton, NJ 08544

August 1990

Reproduction in whole or in part is permitted for
any purpose of the United States Government

This document has been approved for public release
and sale; its distribution is unlimited

Principal Investigator
John K. Gillham
(609) 452-4694

DTIC
ELECTE
AUG 28 1990
S B D
12

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM															
1 REPORT NUMBER Technical Report #22	2 GOVT ACCESSION NO. N/A	3 RECIPIENT'S CATALOG NUMBER N/A															
4 TITLE (and Subtitle) FINAL REPORT		5 TYPE OF REPORT & PERIOD COVERED Final 02/01/84 to 09/30/90															
		6 PERFORMING ORG. REPORT NUMBER															
7 AUTHOR(s) J. K. Gillham		8 CONTRACT OR GRANT NUMBER N00014-84-K-0021															
9 PERFORMING ORGANIZATION NAME AND ADDRESS Polymer Materials Program Department of Chemical Engineering Princeton University, Princeton, NJ 08544		10 PROGRAM ELEMENT PROJECT TASK AREA & WORK UNIT NUMBERS															
11 CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Attn: Code 413, 800 N. Quincy St. Arlington, VA 22217		12 REPORT DATE September 1990															
		13 NUMBER OF PAGES 8															
14 MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15 SECURITY CLASS (of this report) Unclassified															
		15a DECLASSIFICATION/DOWNGRADING SCHEDULE															
16 DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.																	
17 DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) N/A																	
18 SUPPLEMENTARY NOTES																	
19 KEY WORDS (Continue on reverse side if necessary and identify by block number) <table border="0"> <tr> <td>Epoxies</td> <td>Vitrification</td> <td>Water Absorption</td> </tr> <tr> <td>Cure</td> <td>Gelation</td> <td>TTT Cure Diagram</td> </tr> <tr> <td>Kinetics</td> <td>Glass Transition Temperature</td> <td>Anomalous RT Properties</td> </tr> <tr> <td>Chemical Control</td> <td>Physical Aging</td> <td></td> </tr> <tr> <td>Diffusion Control</td> <td>Torsional Braid Analysis</td> <td></td> </tr> </table>			Epoxies	Vitrification	Water Absorption	Cure	Gelation	TTT Cure Diagram	Kinetics	Glass Transition Temperature	Anomalous RT Properties	Chemical Control	Physical Aging		Diffusion Control	Torsional Braid Analysis	
Epoxies	Vitrification	Water Absorption															
Cure	Gelation	TTT Cure Diagram															
Kinetics	Glass Transition Temperature	Anomalous RT Properties															
Chemical Control	Physical Aging																
Diffusion Control	Torsional Braid Analysis																
20 ABSTRACT (Continue on reverse side if necessary and identify by block number) Contributions to the following topics have been reported: 1) Torsional Pendulum/Torsional Braid Analysis; 2) Time-Temperature-Transformation (TTT) Cure Diagram; 3) The Glass Transition Temperature (Tg) as an Index for Monitoring Cure; 4) Anomalous Behavior of Thermosetting Polymers: Properties at Room Temperature Vs. Time and Temperature of Cure; 5) Physical Aging of Thermosetting Systems.																	

FINAL REPORT: OFFICE OF NAVAL RESEARCH
 CONTRACT N00014-84-K-0021
 SUMMARY

The following short sections (I-V) summarize the thrust and conclusions of developments which have been supported at least in part by the ONR Contract. Reference numbers [] refer to the numbering of Technical Reports.

I. TORSIONAL PENDULUM/TORSIONAL BRAID ANALYSIS [2,3]

The freely oscillating torsion pendulum (TP), which is the simplest and perhaps the most sensitive dynamic mechanical technique for characterizing polymers, is used in the quantitative mode to provide shear moduli (storage and loss) data of solid specimens vs. temperature or lapsed time. The scope is extended with advantage in the torsional braid analysis (TBA) mode which uses a composite specimen, made simply by impregnating a glass braid substrate with fluid (e.g., a polymer in a volatile solvent). TBA provides information on chemical and physical transformations over a wide range of conditions (e.g., from liquid to solid and vice versa). The TBA technique has been used principally with thermosetting systems. Developments on thermosetting systems which have arisen in our laboratory from using the TBA technique are summarized in the following sections. It is noted that the TBA/TP technique was the first commercially available automated dynamic mechanical analyzer which, as such, spawned other commercial systems.

II. TIME-TEMPERATURE-TRANSFORMATION (TTT) CURE DIAGRAM [10,21]

A general model for thermosetting materials which relates polymerization to properties has been developed. It arose from the ability of TBA experiments to distinguish between, and measure, the times to gelation and to vitrification. In this, a time-temperature-transformation (TTT) cure diagram relates the various states of matter encountered [i.e., liquid; sol/gel and gel rubber; sol, sol/gel and gel glass] to gelation and vitrification phenomena. The model is extended to rubber-modified thermosetting systems to show that a given chemical formulation can provide different morphologies through different cure procedures, and hence provide different material behavior. It is also extended to high temperature polymers where polymerization and degradation reactions compete. A kinetic equation which accounts for the change from liquid to glass in terms of both chemical and diffusion rate constants has been developed and used to calculate an extended isothermal TTT cure diagram for the reaction of a difunctional aromatic diglycidyl epoxy with a tetrafunctional aromatic diamine.



Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

III. THE GLASS TRANSITION TEMPERATURE (T_g) AS AN INDEX FOR MONITORING CURE [21]

The TBA technique can readily measure the glass transition temperature of thermosetting systems from that of the unreacted formulation (T_{g0}) to that of the fully cured system ($T_{g\infty}$) to within 0.5°C . Since T_g can change more than 200°C during cure, the TBA technique provides good resolution throughout the process of cure.

T_g is the principal parameter for thermosetting systems. Since T_g increases nonlinearly with conversion with T_g being related to conversion in a one-to-one manner, and is easily measured, it is a very useful and sensitive parameter for monitoring both the progress and properties of cure; furthermore, since vitrification is defined to occur when $T_g = T_{\text{cure}}$ (the temperature of cure), it is the basis of the vitrification contour in the time-temperature-transformation (TTT) cure diagram. The progress of cure in the TTT cure diagram can be documented as a series of iso- T_g contours: for epoxies prior to vitrification the reaction is kinetically chemically controlled; after vitrification the reaction becomes diffusion controlled. The basis for the one-to-one relationship between T_g and conversion is that all of the crosslinking sites are in effect trifunctional.

IV. ANOMALOUS BEHAVIOR OF THERMOSETTING POLYMERS: PROPERTIES AT ROOM TEMPERATURE VS. TIME AND TEMPERATURE OF CURE [8,15,20]

TBA and TP data show that the modulus in the glassy state (e.g., at 25°C) decreases with increased cure in spite of the increased crosslinking density. A summary of our investigations on the ramifications of this anomaly follows.

The room temperature density (ρ_{RT}) of a difunctional aromatic dpoxy resin cured with a tetrafunctional aromatic amine passes through a maximum value with increasing conversion. Cure results in a unique value of ρ_{RT} for each conversion as long as the material does not vitrify on cure. The occurrence of vitrification during cure eliminates the one-to-one relationship because of the non-equilibrium nature of the glass transition region and of the glassy state. Prolonged isothermal cure to well beyond vitrification results in limiting values of ρ_{RT} which decrease with increasing temperature of cure. The maximum in the ρ_{RT} vs. conversion relationship is explained in terms of 1) the effects on the free volume of shrinkage due to cure and of the corresponding increase in the glass transition temperature and 2) the effect of increasing average relaxation times in the vicinity of the glass transition with increasing T_g which affects the physical aging process on cooling through T_g . The effect of the anomalous behavior of density gives rise to parallel anomalous behavior in other material properties, for example in modulus, stresses in composites, and absorption of water.

V. PHYSICAL AGING OF THERMOSETTING SYSTEMS [18]

The current limitation to the quality of data in the TBA/TP technique is temperature control, which is currently to less than $\pm 0.1^\circ\text{C}$ by using a large copper block. Data are excellent at a scale expansion of 30 times that of conventional presentation.

The sensitivity of the TP and TBA techniques is demonstrated by data on isothermal physical aging ("annealing") deep into the glassy state (i.e., $T_a \ll T_g$). For a fully cured epoxy system, the rate of annealing (as measured by the rate of change of modulus) is measurable and constant for a wide temperature range of more than 100°C between T_g and T_β ($T_\beta < T_g$). Perturbations in the thermomechanical behavior after annealing at T_a are restricted to a narrow range in the vicinity of T_a . A single specimen was used for successive annealing experiments (the effect of prior annealing was eliminated by heating to above T_g). Use of a single specimen provides an internal control for comparing the effects of aging versus the unaged specimen.

Comparison of physical aging at 50°C (i.e., $T_a \ll T_g$) vs. extent of cure for a high T_g liquid thermosetting dicyanate ester/polycyanurate system showed that in this system the rate of annealing decreased with increasing conversion (T_g) in spite of the initial modulus at 50°C decreasing with increased conversion (T_g). This showed that the free volume accessible for molecular relaxation decreases with increasing crosslinks in spite of the corresponding decrease in density.

FINAL REPORT: OFFICE OF NAVAL RESEARCH
CONTRACT N00014-84-K-0021

LIST OF TECHNICAL REPORTS AND JOURNAL ARTICLES:

Technical Report No. 1 June 1984

"The Transformation of Liquid to Amorphous Solid: The Time to Vitri-
fy for Styrene Polymerization"

M. T. Aronhime and J. K. Gillham

AD Number AD-A143228

Published in *Journal of Applied Polymer Science*, Vol. 29, 1027-2020
(1984).

Technical Report No. 2 October 1984

"Rubber-Modified Epoxies: I. Cure, Transitions and Morphology"

L. C. Chan, J. K. Gillham, A. J. Kinloch and S. J. Shaw

AD Number A147377

Published in *Rubber-Modified Thermoset Resins* (Editors, C. K. Riew and
J. K. Gillham), *American Chemical Society, Advances in Chemistry*
Series, Number 208, Ch. 14, pp. 235-260 (1985).

Technical Report No. 3 October 1984

"Rubber-Modified Epoxies: II. Morphology, Transitions and Mechanical
Properties"

L. C. Chan, J. K. Gillham, A. J. Kinloch and S. J. Shaw

AD Number A147962

Published in *Rubber-Modified Thermoset Resins* (Editors, C. K. Riew and
J. K. Gillham), *American Chemical Society, Advances in Chemistry*
Series, Number 208, Ch. 15, pp. 261-279 (1985).

Technical Report No. 4 June 1985

"Cure and Properties of Thermosetting Systems"

J. K. Gillham

AD Number A157100

Published in *British Polymer Journal*, Vol. 17, No. 2, pp. 224-226
(1985).

Technical Report No. 5 December 1985

"Time-Temperature-Transformation (TTT) Cure Diagrams: Relationship
Between T_g and the Temperature and Time of Cure for Epoxy Resins"

X. Peng and J. K. Gillham

AD Number A162428

Published in *Journal of Applied Polymer Science*, Vol. 30, pp. 4685-4694
(1985).

Technical Report No. 6 December 1985

"The Time-Temperature-Transformation (TTT) Cure Diagram of
Thermosetting Systems"

M. T. Aronhime and J. K. Gillham

AD Number not provided

Published in *Advances in Polymer Science*, Vol. 78, pp. 83-113 (1986).

Technical Report No. 7 March 1986

"Curing"

J. K. Gillham

AD Number A165815

Published in *Encyclopedia of Polymer Science and Engineering*, 2nd Edition, Vol. 4, pp. 519-524 (1986).

Technical Report No. 8 May 1986

"Effect of Time-Temperature Path of Cure on the Water Absorption of High T_g Epoxy Resins"

M. T. Aronhime, X. Peng, J. K. Gillham and R. D. Small

AD Number A168106

Published in *Journal of Applied Polymer Science*, Vol. 32, pp. 3589-3626. *Ibid*, p. 6353 (1986).

Technical Report No. 9 January 1987

"Cure and Properties of Thermosetting Polymers"

J. K. Gillham

AD Number A175895

Published in *Structural Adhesives: Developments in Resins and Primers* (Ed., A. J. Kinloch), pp. 1-27. Elsevier Applied Science Publishers, London, 1986.

Technical Report No. 10 January 1987

"Formation and Properties of Thermosetting and High T_g Polymeric Materials"

J. K. Gillham

AD Number A175896

Published in *Polymer Engineering and Science*, Vol. 26, No. 20, pp. 1429-1433 (1986).

Technical Report No. 11 July 1987

"Formation and Properties of Thermosetting and High T_g Polymeric Materials"

J. K. Gillham

AD Number A183132

Published in *Makromol. Chem., Macromol. Symp.*, Vol. 7, pp. 67-74 (1987).

Technical Report No. 12 July 1987

"Time-Temperature-Transformation (TTT) Cure Diagrams: Relationship Between T_g and the Temperature and Time of Cure for a Polyamic Acid/Polyimide System"

G. R. Palmese and J. K. Gillham

AD Number A183385

Published in *Journal of Applied Polymer Science* Vol. 34, pp. 1925-1939 (1987).

Technical Report No. 13 January 1988

"The Time-Temperature-Transformation (TTT) Diagram as a Basis for Relating the Formation and Properties of Reactive Coatings"

J. K. Gillham

AD Number A190872

Presented as the Plenary Lecture at the Water-Borne and Higher Solids Coatings Symposium, Proceedings, pp. 1-22, February 3, 1988, New Orleans, LA.

Technical Report No. 14 June 1988

"A Methodology for Characterizing Reactive Coatings: Time-Temperature-Transformation [TTT] Analysis of the Competition Between Cure, Evaporation and Thermal Degradation for an Epoxy-Phenolic System"

S. Gan, J. K. Gillham and R. P. Prime

Published in Journal of Polymer Science, Vol. 37, pp. 803-816 (1989).

AD Number A197254

Technical Report No. 15 July 1988

"Anomalous Behavior of Cured Epoxy Resins: Density at Room Temperature Vs. Time and Temperature of Cure"

K. P. Pang and J. K. Gillham

AD Number A197644

Published in Journal of Applied Polymer Science, Vol. 37, pp. 1969-1991 (1989).

Technical Report No. 16 February 1989

"The Glass Transition Temperature as a Parameter for Monitoring the Isothermal Cure of an Amine-Cured Epoxy System"

G. Wisanrakkit and J. K. Gillham

AD Number A204307

To be published in American Chemical Society, Advances in Chemistry Series (1990).

Technical Report No. 17 February 1989

"The Glass Transition Temperature (T_g) as a Parameter for Monitoring the Cure of an Amine-Cured Epoxy System at Constant Heating Rates"

G. Wisanrakkit, J. K. Gillham and J. B. Enns

AD Number A206098

To be published in the Journal of Applied Polymer Science (1990).

Technical Report No. 18 March 1989

"Annealing Studies on a Fully Cured Epoxy Resin: Effect of Thermal Prehistory, and Time and Temperature of Annealing"

K. P. Pang and J. K. Gillham

AD Number A205875

Published in the Journal of Applied Polymer Science, Vol. 38, pp. 2115-2130 (1990).

Technical Report No. 19 March 1989

"Effect of Physical Annealing on the Dynamic Mechanical Properties of a High T_g Amine-Cured Epoxy System"

G. Wisanrakkit and J. K. Gillham

AD Number A205980

To be published in the Journal of Applied Polymer Science (1990).

Technical Report No. 20 June 1989

"Anomalous Stresses Vs. Extent of Cure in an Epoxy Composite Specimen"

M. A. Taylor and J. K. Gillham

AD Number A208523

Published in American Chemical Society, Proceedings, Division of Polymeric Materials Science and Engineering, Vol. 61, 806-814 (1989).

Also, to be published in the Journal of Applied Polymer Science (1991).

Technical Report No. 21 August 1990

"The Glass Transition Temperature (T_g) as an Index of Chemical Conversion for a High-T_g Amine/Epoxy System: Chemical and Diffusion Controlled Reaction Kinetics"

G. Wisanrakkit and J. K. Gillham

AD Number Not Received.

Published in Journal of Coatings Technology, Vol. 62, No. 783, pp. 35-50, April 1990.

Technical Report No. 22 September 1990

FINAL REPORT Covering PERIOD 2/1/84 to 9/30/90.

FINAL REPORT: OFFICE OF NAVAL RESEARCH
CONTRACT N00014-84-K-0021

LIST OF PERSONNEL

M. T. Aronhime, Ph.D. Graduate Student
L. C. Chan, Ph.D. Graduate Student
X. Peng, Visiting Scholar
G. R. Palmese, B.S.E. Undergraduate Student
S. Gan, Visiting Scholar
K. P. Pang, Ph.D. Graduate Student
G. Wisanrakkit, Ph.D. Graduate Student
M. A. Taylor, M.S.E. Graduate Student
S. Simon, Ph.D. Graduate Student
R. A. Venditti, Ph.D. Graduate Student
J. K. Gillham, Professor (Principal Investigator).

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	<u>No. Copies</u>		<u>No. Copies</u>
Office of Naval Research Attn: Code 1113 800 N. Quincy Street Arlington, Virginia 22217-5000	2	Dr. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 50C Crane, Indiana 47522-5050	1	Naval Weapons Center Attn: Dr. Ron Atkins Chemistry Division China Lake, California 93555	1
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko, Code L52 Port Hueneme, California 93401	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12 high quality	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 27709	1
DTNSRDC Attn: Dr. H. Singerman Applied Chemistry Division Annapolis, Maryland 21401	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 19112	1
Dr. William Tolles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375-5000	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1